

murales

ombrellone a braccio laterale addossato
in alluminio verniciato grigio antracite
lateral arm parasol attached to the wall
in aluminium anthracite grey



CARATTERISTICHE TECNICHE TECHNICAL DATA

parti metalliche prima zincate,
poi verniciate
metal parts galvanized and
varnished

stecche intercambiabili
interchangeable ribs

possibilità di posizionamento
aderente alla parete di aggancio
placement attached to the wall

predisposizione per aggancio
tramite tirante acciaio (operazione
consigliata)
prepared for docking by steel cable
(recommended)

OPTIONALS

finitura pendente:
flounce finishing:

 merletti
crenelation

 onde
wave



Fissaggio consigliato

In presenza di cemento armato:

Fischer Ø 10

If wall is in reinforced concrete:

Fischer Ø 10

In presenza di bimattone:

Fischer con gabbia + chimico

If wall is in perforated brick:

Fischer with cage + chemical fixing





In presenza di cappotto:

barre filettate Ø 10

If wall is with coat:

Threaded bars Ø 10



DIMENSIONE / SIZE	2x2	2,5x2,5	3x3	2x3
				
PALO (cm) / POLE	7,2x7,2	7,2x7,2	7,2x7,2	7,2x7,2
STECCHIE (NR.) / RIBS	4	4	8	6
PENDENTE / FLOUCE	•	•	•	•
TESSUTO / FABRIC	•	•	•	•
Acilico - Tempotest® Parà Ombrelloni Acrylic - Tempotest® Parà Parasols				

*Quote e dimensioni indicative, espresse in cm / Highs and dimensions are indicatives and expressed in cm